Method 21--Determination of Volatile Organic Compounds Leaks

- 1. Applicability and Principle
 - 1.1 Applicability. This method applies to the determination of volatile organic compound (VOC) leaks from process equipment. These sources include, but are not limited to, valves, flanges and other connections, pumps and compressors, pressure relief devices, process drains, open-ended valves, pump and compressor seal system degassing vents, accumulator vessel vents, agitator seals, and access door seals.
 - 1.2 Principle. A portable instrument is used to detect VOC leaks from individual sources. The instrument detector type is not specified, but it must meet the specifications and performance criteria contained in Section 3. A leak definition concentration based on a reference compound is specified in each applicable regulation. This procedure is intended to locate and classify leaks only, and is not to be used as a direct measure of mass emission rates from individual sources.

2. Definitions

- 2.1 Leak Definition Concentration. The local VOC concentration at the surface of a leak source that indicates that a VOC emission (leak) is present. The leak definition is an instrument meter reading based on a reference compound.
- 2.2 Reference Compound. The VOC species selected as an instrument calibration basis for specification of the leak definition concentration. (For example: If a leak definition concentration is 10,000 ppmv as methane, then any source emission that results in a local concentration that yields a meter reading of 10,000 on an instrument calibrated with methane would be classified as a leak. In this example, the leak definition is 10,000 ppmv, and the reference compound is methane.)
- 2.3 Calibration Gas. The VOC compound used to adjust the instrument meter reading to a known value. The calibration gas is usually the reference compound at a concentration approximately equal to the leak definition concentration:
- 2.4 No Detectable Emission. Any VOC concentration at a potential leak source (adjusted for local VOC ambient concentration) that is less than a value corresponding to the instrument readability specification of section 3.1.1© indicates that a leak is not present.
- 2.5 Response Factor. The ratio of the known concentration of a VOC compound to the observed meter reading when measured using an instrument calibrated with the reference compound specified in the application regulation.
- 2.6 Calibration Precision. The degree of agreement between measurements of the same known value, expressed as the relative percentage of the average difference between the meter readings and the known concentration to the known concentration.

2.7 Response Time. The time interval from a step change in VOC concentration at the input of the sampling system to the time at which 90 percent of the corresponding final value is reached as displayed on the instrument readout meter.

3. Apparatus

3.1 Monitoring Instrument.

3.1.1 Specifications.

- a. The VOC instrument detector shall respond to the compounds being processed. Detector types which may meet this requirement include, but are not limited to, catalytic oxidation, flame ionization, infrared absorption, and photoionization.
- b. Both the linear response range and the measurable range of the instrument for each of the VOC to be measured, and for the VOC calibration gas that is used for calibration, shall encompass the leak definition concentration specified in the regulation. A dilution probe assembly may be used to bring the VOC concentration within both ranges; however, the specifications for instrument response time and sample probe diameter shall still be met.
- c. The scale of the instrument meter shall be readable to ñ2.5 percent of the specified leak definition concentration when performing a no detectable emission survey.
- d. The instrument shall be equipped with an electrically driven pump to insure that a sample is provided to the detector at a constant flow rate. The nominal sample flow rate, as measured at the sample probe tip, shall be 0.10 to 3.0 liters per minute when the probe is fitted with a glass wool plug or filter that may be used to prevent plugging of the instrument.
- e. The instrument shall be intrinsically safe as defined by the applicable U.S.A. standards (e.g., National Electric Code by the National Fire Prevention Association) for operation in any explosive atmospheres that may be encountered in its use. The instrument shall, at a minimum, be intrinsically safe for Class 1, Division 1 conditions, and Class 2, Division 1 conditions, as defined by the example Code. The instrument shall not be operated with any safety device, such as an exhaust flame arrestor, removed.
- f. The instrument shall be equipped with a probe or probe extension for sampling not to exceed in. in outside diameter, with a single end opening for admission of sample.

3.1.2 Performance Criteria.

- (a) The instrument response factors for each of the VOC to be measured shall be less than 10. When no instrument is available that meets this specification when calibrated with the reference VOC specified in the applicable regulation, the available instrument may be calibrated with one of the VOC to be measured, or any other VOC, so long as the instrument then has a response factor of less than 10 for each of the VOC to be measured.
- (b) The instrument response time shall be equal to or less than 30 seconds. The instrument pump, dilution probe (if any), sample probe, and probe filter, that will be used during testing, shall all be in place during the response time determination.
- c. The calibration precision must be equal to or less than 10 percent of the calibration gas value.
- d. The evaluation procedure for each parameter is given in Section 4.4.

3.1.3 Performance Evaluation Requirements.

- a. A response factor must be determined for each compound that is to be measured, either by testing or from reference sources. The response factor tests are required before placing the analyzer into service, but do not have to be repeated at subsequent intervals.
- b. The calibration precision test must be completed prior to placing the analyzer into service, and at subsequent 3-month intervals or at the next use whichever is later.
- c. The response time test is required prior to placing the instrument into service. If a modification to the sample pumping system or flow configuration is made that would change the response time, a new test is required prior to further use.
- 3.2 Calibration Gases. The monitoring instrument is calibrated in terms of parts per million by volume (ppmv) of the reference compound specified in the applicable regulation. The calibration gases required for monitoring and instrument performance evaluation are a zero gas (air, less than 10 ppmv VOC) and a calibration gas in air mixture approximately equal to the leak definition specified in the regulation. If cylinder calibration gas mixtures are used, they must be analyzed and certified by the manufacturer to be within ñ2 percent accuracy, and a shelf life must be specified. Cylinder standards must be either reanalyzed or replaced at the end of the specified shelf life. Alternately, calibration gases may be prepared by the user according to any accepted gaseous standards preparation procedure that will yield a mixture accurate to

within ñ2 percent. Prepared standards must be replaced each day of use unless it can be demonstrated that degradation does not occur during storage.

Calibrations may be performed using a compound other than the reference compound if a conversion factor is determined for that alternative compound so that the resulting meter readings during source surveys can be converted to reference compound results.

4. Procedures

4.1 Pretest Preparations. Perform the instrument evaluation procedures given in Section 4.4 if the evaluation requirements of Section 3.1.3 have not been met.

4.2 Calibration Procedures. Assemble and start up the VOC analyzer according to the manufacturer's instructions. After the appropriate warmup period and zero internal calibration procedure, introduce the calibration gas into the instrument sample probe. Adjust the instrument meter readout to correspond to the calibration gas value.

Note: If the meter readout cannot be adjusted to the proper value, a malfunction of the analyzer is indicated and corrective actions are necessary before use.

4.3 Individual Source Surveys.

- 4.3.1 Type I—Leak Definition Based on Concentration. Place the probe inlet at the surface of the component interface where leakage could occur. Move the probe along the interface periphery while observing the instrument readout. If an increased meter reading is observed, slowly sample the interface where leakage is indicated until the maximum meter reading is obtained. Leave the probe inlet at this maximum reading location for approximately two times the instrument response time. If the maximum observed meter reading is greater than the leak definition in the applicable regulation, record and report the results as specified in the regulation reporting requirements. Examples of the application of this general technique to specific equipment types are:
 - a. Valves—The most common source of leaks from valves is at the seal between the stem and housing. Place the probe at the interface where the stem exits the packing gland and sample the stem circumference. Also, place the probe at the interface of the packing gland take-up flange seat and sample the periphery. In addition, survey valve housings of multipart assembly at the surface of all interfaces where a leak could occur.

 Flanges and Other Connections—For welded flanges, place the probe at the outer edge of the flange-gasket interface and sample the circumference

- of the flange. Sample other types of nonpermanent joints (such as threaded connections) with a similar traverse.
- c. Pumps and Compressors—Conduct a circumferential traverse at the outer surface of the pump or compressor shaft and seal interface. If the source is a rotating shaft, position the probe inlet within 1 cm of the shaft-seal interface for the survey. If the housing configuration prevents a complete traverse of the shaft periphery, sample all accessible portions. Sample all other joints on the pump or compressor housing where leakage could occur.
- d. Pressure Relief Devices—The configuration of most pressure relief devices prevents sampling at the sealing seat interface. For those devices equipped with an enclosed extension, or horn, place the probe inlet at approximately the center of the exhaust area to the atmosphere.
- e. Process Drains—For open drains, place the probe inlet at approximately the center of the area open to the atmosphere. For covered drains, place the probe at the surface of the cover interface and conduct a peripheral traverse.
- f. Open-Ended Lines or Valves—Place the probe inlet at approximately the center of the opening to the atmosphere.
- g. Seal System Degassing Vents and Accumulator Vents—Place the probe inlet at approximately the center of the opening to the atmosphere.
- h. Access Door Seals—Place the probe inlet at the surface of the door seal interface and conduct a peripheral traverse.

4.3.2 Type II—"No Detectable Emission".

Determine the local ambient concentration around the source by moving the probe inlet randomly upwind and downwind at a distance of one to two meters from the source. If an interference exists with this determination due to a nearby emission or leak, the local ambient concentration may be determined at distances closer to the source, but in no case shall the distance be less than 25 centimeters. Then move the probe inlet to the surface of the source and determine the concentration described in 4.3.1. The difference between these concentrations determines whether there are no detectable emissions. Record and report the results as specified by the regulation.

For those cases where the regulation requires a specific device installation, or that specified vents be ducted or piped to a control device, the existence of these conditions shall be visually confirmed. When the regulation also requires that no detectable emissions exist, visual observations and sampling surveys are required. Examples of this technique are:

(a) Pump or Compressor Seals—If applicable, determine the type of shaft seal. Preform a survey of the local area ambient VOC concentration and determine if detectable emissions exist as described above.

- (b) Seal System Degassing Vents, Accumulator Vessel Vents, Pressure Relief Devices—If applicable, observe whether or not the applicable ducting or piping exists. Also, determine if any sources exist in the ducting or piping where emissions could occur prior to the control device. If the required ducting or piping exists and there are no sources where the emissions could be vented to the atmosphere prior to the control device, then it is presumed that no detectable emissions are present. If there are sources in the ducting or piping where emissions could be vented or sources where leaks could occur, the sampling surveys described in this paragraph shall be used to determine if detectable emissions exist.
- 4.3.3 Alternative Screening Procedure. A screening procedure based on the formation of bubbles in a soap solution that is sprayed on a potential leak source may be used for those sources that do not have continuously moving parts, that do not have surface temperatures greater than the boiling point or less than the freezing point of the soap solution, that do not have open areas to the atmosphere that the soap solution cannot bridge, or that do not exhibit evidence of liquid leakage. Sources that have these conditions present must be surveyed using the instrument techniques of 4.3.1 or 4.3.2.

Spray a soap solution over all potential leak sources. The soap solution may be a commercially available leak detection solution or may be prepared using concentrated detergent and water. A pressure sprayer or a squeeze bottle may be used to dispense the solution. Observe the potential leak sites to determine if any bubbles are formed. If no bubbles are observed, the source is presumed to have no detectable emissions or leaks as applicable. If any bubbles are observed, the instrument techniques of 4.3.1 or 4.3.2 shall be used to determine if a leak exists, or if the source has detectable emissions, as applicable.

- 4.4 Instrument Evaluation Procedures. At the beginning of the instrument performance evaluation test, assemble and start up the instrument according to the manufacturer's instructions for recommended warmup period and preliminary adjustments.
 - 4.4.1 Response Factor. Calibrate the instrument with the reference compound as specified in the applicable regulation. For each organic species that is to be measured during individual source surveys, obtain or prepare a known standard in air at a concentration of approximately 80 percent of the applicable leak definition unless limited by volatility or explosivity. In these cases, prepare a standard at 90 percent of the saturation concentration, or 70 percent of the lower explosive limit, respectively. Introduce this mixture to the analyzer and record the observed meter reading. Introduce zero air until a stable reading is obtained. Make a total of three measurements by alternating between the

known mixture and zero air. Calculate the response factor for each repetition and the average response factor.

Alternatively, if response factors have been published for the compounds of interest for the instrument or detector type, the response factor determination is not required, and existing results may be referenced. Examples of published response factors for flame ionization and catalytic oxidation detectors are included in Bibliography.

4.4.2 Calibration Precision. Make a total of three measurements by alternately using zero gas and the specified calibration gas. Record the meter readings. Calculate the average algebraic difference between the meter readings and the known value. Divide this average difference by the known calibration value and mutiply by 100 to express the resulting calibration precision as a percentage.

4.4.3 Response Time. Introduce zero gas into the instrument sample probe. When the meter reading has stabilized, switch quickly to the specified calibration gas. Measure the time from switching to when 90 percent of the final stable reading is attained. Perform this test sequence three times and record the results. Calculate the average response time.

5. Bibliography

- DuBose, D.A., and G.E. Harris. Response Factors of VOC Analyzers at a Meter Reading of 10,000 ppmv for Selected Organic Compounds. U.S. Environmental Protection Agency, Research Triangle Park, NC. Publication No. EPA 600/2-81-051. September 1981.
- Brown, G.E., et al. Response Factors of VOC Analyzers Calibrated with Methane for Selected Organic Compounds. U.S. Environmental Protection Agency, Research Triangle Park, NC. Publication No. EPA 600/2-81-022. May 1981.
- DuBose, D.A., et al. Response of Portable VOC Analyzers to Chemical Mixtures. U.S. Environmental Protection Agency, Research Triangle Park, NC. Publication No. EPA 600/2-81-110. September 1981.

8.21 HAZARDOUS WASTE STORAGE TANKS - TABLE B-2

| 42222 | | ************ | | *************** | | | |
|-------|----------|----------------|--------|------------------|---------------------|----------|----------|
| | Tag | Unit | Eq | Component | LOCATION | | |
| | | | Size | • | DOCATION | Iso | Class |
| | | | | | ••••• | | |
| | PBZ05000 | C-AREA RESIDUE | | PUMP | BOTTOMS PUMP E.OF C | | |
| | PBZ05004 | C-AREA RESIDUE | 1" | FLANGED FITTINGS | BOTTOMS PUMP E.OF C | DWG00008 | |
| | PBZ05005 | C-AREA RESIDUE | 1" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05006 | C-AREA RESIDUE | 1" | FLANGED FITTINGS | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05010 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05015 | C-AREA RESIDUE | 1" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05020 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05025 | C-AREA RESIDUE | 1" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05030 | C-AREA RESIDUE | 1" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05035 | C-AREA RESIDUE | 3" | PLUG VALVE | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05040 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05045 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05050 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05055 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05060 | C-AREA RESIDUE | 3" | PLUG VALVE | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05065 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | BOTTOMS PUMP E.OF C | DWG00008 | HL |
| | PBZ05068 | C-AREA RESIDUE | 3" | FLANGED FITTINGS | BOTTOM OF BOTTOMS T | DWG00008 | HL |
| | PBZ05070 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05075 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | CUTSIDE E. OF C-12 | DWG00008 | HL. |
| | PBZ05080 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05085 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05087 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05090 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL. |
| | PBZ05095 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05098 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05100 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05105 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05110 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05115 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL HL |
| | PBZ05120 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05125 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05130 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05135 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | HL |
| | PBZ05140 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | DWG00008 | |
| | PBZ05145 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | OUTSIDE E. OF C-12 | | HL |
| | PBZ05150 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | 2ND FLOOR OF C-12 | DWG00008 | |
| | PBZ05155 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | 2ND FLOOR OF C-12 | DWG00008 | |
| | PBZC5160 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05165 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05170 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05175 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05180 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05185 | C-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | TRAILER LOADING | DWG00008 | |
| | PBZ05190 | C-AREA RESIDUE | 1 1/2" | PLUG VALVE | TRAILER LOADING PAD | DWG00008 | |
| | PCS00005 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | VENT LINE 4TH FL. | DWG00006 | |
| | PCS00010 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | VENT LINE 3RD FL. | DWG00006 | |
| | PCS00015 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | VENT LINE 2ND FL. | DWG00004 | |
| | PCS00020 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | ABOVE STORAGE TANK | DWG00004 | |
| | PCS00025 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | ABOVE STORAGE TANK | DWG00004 | |
| | | | | | | | - |

| *********** | | *********** | | | | |
|-------------|--|---------------|------------------|---------------------------------------|----------------------|-------|
| Tag | Unit | Eq | Component | LOCATION | Iso | |
| | | Size | | | 130 | Class |
| ••••• | • | | | | | |
| PCS00030 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTING | | DWG00004 | |
| PCS00035 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTING | S ABOVE STORAGE TANK | DWG00004 | LL |
| PCS00040 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTING | S TOP OF DECH+ STOR TK | DWG00004 | LL |
| PCS00045 | DECH+ RESIDUE | 4 " | FLANGED FITTING | | DWG00004 | LL |
| PCS00050 | DECH+ RESIDUE | 3" | FLANGED FITTING | | DWG00005 | LL |
| PCS00055 | DECH+ RESIDUE | 3" | FLANGED FITTING | | DWG00005 | LL |
| PCS00060 | DECH+ RESIDUE | 2" | PLUG VALVE | TRAILER LOADING | DWG00007 | LL |
| PCS00065 | DECH- RESIDUE | 2 " | PLUG VALVE | TRAILER LOADING | DWG00007 | LL |
| PCS00085 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | | DWG00004 | G/V |
| PCS00095 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | | DWG00004 | |
| PCS00100 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00105 | DECH- RESIDUE | 3" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00110 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | | | LL |
| PCS00115 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00120 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00125 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00130 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | | DWG00004 | LL. |
| PCS00135 | DECH+ RESIDUE | 1 1/2" | FLANGED FITTINGS | | DWG00004 | LL |
| PCS00140 | DECH+ RESIDUE | 4" | FLANGED FITTINGS | | DWG00004 DWG00004 | LL |
| PCS00145 | DECH+ RESIDUE | 4" | FLANGED FITTINGS | | | G/V |
| PCS00150 | DECH+ RESIDUE | 4" | FLANGED FITTINGS | | DWG00004 | G/V |
| PCS00155 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | TANK | DWG00004 | G/V |
| PCS00160 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | THE STOR IN | DWG00004 | LL |
| PCS00165 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | THE THE SIME | DWG00005 | LL |
| PCS00170 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | - Dive 1 DDD DIVE | DWG00005 | LL |
| PCS00175 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00184 | DECH+ RESIDUE | 1" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | DWG00005 | LL |
| PCS00185 | DECH+ RESIDUE | 3/4" X 1 1/2" | SAMPLE VALVE | | DWG00003 | LL |
| PCS00186 | DECH- RESIDUE | 1" | FLANGED FITTINGS | DECH RESIDUE PUMP | DWG00003 | LL |
| PCS00188 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00190 | DECH+ RESIDUE | 2" | PLUG VALVE | DECH+ RESIDUE PUMP DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00192 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | | LL |
| PCS00194 | DECH+ RESIDUE | 2" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | | LL |
| PCS00195 | DECH+ RESIDUE | 2" | PLUG VALVE | | DWG00003 | |
| PCS00196 | Carried States Control of the Contro | 2" | | DECH+ RESIDUE PUMP DECH+ RESIDUE PUMP | DWG00003 | |
| PCS00200 | DECH+ RESIDUE | | PLUG VALVE | | DWG00003 | |
| | DECH+ RESIDUE | | FLANGED FITTINGS | | DWG00003 | |
| | | | FLANGED FITTINGS | | DWG00004 | |
| | | | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| | | | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| | | | | | DWG00004 | |
| | | | PLUG VALVE | TOP OF DECH+ STOR TK | DWG00004 | |
| | | 3" | VALVE | | DWG00004 | |
| | | 3" | | | DWG00004 | |
| | | | VALVE | | DWG00004 | |
| | DECH- RESIDUE | | PLUG VALVE | | DWG00004 | |
| | | | | DOM OR 11911 | DWG00004 | |
| | | | | MOD OR DEGU | DWG00004 | |
| | | | PLUG VALVE | | DWG00004 | |
| FC300232 | Daent KESIDUE | 1 1/2" | FLANGED FITTINGS | BOT OF NEW PERC STIL | DWG00004 | LL |

Pg 3

| | | *********** | | .======= | | |
|-----------|---------------|-------------|-----------------------------------|----------------------|----------|-----------|
| Tag | Unit | Eq | Component | LOCATION | | |
| | | Size | | 20071101 | Iso | Class |
| | | | | | | |
| PCS00254 | DECH+ RESIDUE | 1 1/2" | PLUG VALVE | BOT OF NEW PERC STIL | DWG00004 | |
| PCS00255 | DECH+ RESIDUE | 1 1/2" | PLUG VALVE | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00260 | DECH+ RESIDUE | 3 " | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | 20704 200 |
| PCS00265 | DECH+ RESIDUE | 3 " | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | |
| PCS00270 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00275 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | -,- |
| PCS00280 | DECH+ RESIDUE | 3 " | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00315 | DECH+ RESIDUE | 3 " | CONTROL VALVE | BOT OF DECH+ STOR TK | DWG00003 | LL |
| PCS00320 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | BOT OF DECH+ STOR TK | DWG00003 | LL |
| PCS00325 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | BOT OF DECH+ STOR TK | DWG00003 | LL |
| PCS00330 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | BOT OF DECH+ STOR TK | DWG00003 | LL |
| PCS00335 | DECH+ RESIDUE | 1" | PLUG VALVE | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00358 | DECH+ RESIDUE | 1" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00360 | DECH+ RESIDUE | 1" | PLUG VALVE | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00362 | DECH+ RESIDUE | 1" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00365 | DECH+ RESIDUE | 3" | PLUG VALVE | DECH+ RESIDUE PUMP | DWG00003 | LL |
| PCS00370 | DECH+ RESIDUE | 2" | PLUG VALVE | TRAILER LOADING | DWG00003 | LL |
| PCS00375 | DECH+ RESIDUE | 2" | OPEN END LOADING HOSE | TRAILER LOADING | DWG00007 | LL |
| PCS00380 | DECH+ RESIDUE | 1" | FLANGED FITTINGS | PERC FEED LINE | DWG00007 | LL |
| PCS00385 | DECH+ RESIDUE | 1" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00390 | DECH+ RESIDUE | 1" | BALL VALVE | PERC FEED LINE | DWG00005 | LL |
| PCS00395 | DECH+ RESIDUE | 3" | PLUG VALVE | PERC FEED LINE | DWG00005 | LL |
| PCS00400 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00410 | DECH- RESIDUE | 1" | CHECK VALVE | PERC FEED LINE | DWG00005 | |
| PCS00415 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00420 | DECH+ RESIDUE | 3" | CONTROL VALVE | BOT PERC FEED TK | | LL |
| PCS00425 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00430 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | LL |
| PCS00440 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00005 | LL C/W |
| PCS00445 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | G/V |
| PCS00450 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | G/V |
| PCS00455 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | G/V |
| PCS00460 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | ABOVE STORAGE TANK | DWG00004 | G/V |
| PCS00465 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | ABOVE STORAGE TANK | DWG00004 | G/V |
| PCS00470 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00475 | DECH+ RESIDUE | 3" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| | DECH+ RESIDUE | 6" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| | DECH+ RESIDUE | 3" | PLUG VALVE | PERC FEED LINE | DWG00004 | |
| | DECH- RESIDUE | 1" | PLUG VALVE | | DWG00005 | |
| | | 1 1/2" | FLANGED FITTINGS | PERC FEED LINE | DWG00005 | |
| PCS00500 | DECH- RESIDUE | 1 1/2" | FLANGED FITTINGS | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00510 | DECH+ RESIDUE | - 1/2 | AGITATOR | VENT LINE 4TH FL. | DWG00006 | |
| | DECH+ RESIDUE | | PUMP | TOP OF DECH+ STOR TK | DWG00004 | |
| PCS00518 | DECH- RESIDUE | 2" | FLANGED FITTINGS | DECH+ RESIDUE PUMP | DWG00003 | |
| PCS00523 | DECH+ RESIDUE | 1" | PLUG VALVE | DECH RESIDUE PUMP | DWG00003 | |
| PCS00525 | DECH+ RESIDUE | 1 1/2" | | DECH- RESIDUE PUMP | DWG00003 | |
| PCS00530 | DECH- RESIDUE | 3" | FLANGED FITTINGS FLANGED FITTINGS | VENT LINE 4TH FL. | DWG00006 | |
| PCS00535 | DECH+ RESIDUE | 3" | | VENT LINE 4TH FL. | DWG00006 | |
| PCS00533 | | | FLANGED FITTINGS | VENT LINE 4TH FL. | DWG00006 | |
| - 6300340 | DECH- RESIDUE | 3 " | FLANGED FITTINGS | VENT LINE 4TH FL. | DWG00006 | G/V |

RCRA SUBPART BB EQUIPMENT LIST

| 48 | | | | | | | | | |
|----|----------|----------------|-------------|------------------|---|----------------------|----------|-------|--|
| | Tag | Unit | Eq Size | Component | | LOCATION | Iso | Class | |
| | PCS00545 | DECH+ RESIDUE | 3" | ZIANGED ETEMTNOS | | | | | |
| | | | - | FLANGED FITTINGS | • | VENT LINE 4TH FL. | DWG00006 | G/V | |
| | PCS00550 | DECH+ RESIDUE | 1 1/2" | PLUG VALVE | | VENT LINE 4TH FL. | DWG00006 | G/V | |
| | PDT00005 | N-AREA RESIDUE | 2" | PLUG VALVE | | BOTTOM OF REBOILER | DWG00012 | HL | |
| | PDT00010 | N-AREA RESIDUE | 2" | PLUG VALVE | | BOTTOM OF REBOILER | DWG00012 | | |
| | PDT00015 | N-AREA RESIDUE | 2" | PLUG VALVE | | BOTTTOM OF REBOILER | DWG00012 | HL | |
| | PDT00020 | N-AREA RESIDUE | 2" | PLUG VALVE | | BOTTOM OF REBCILER | DWG00012 | HL | |
| | PDT00025 | N-AREA RESIDUE | 3" | PLUG VALVE | | MCT REBOILER TRANS F | DWG00012 | HL | |
| | PDT00028 | N-AREA RESIDUE | 3/4" | BALL VALVE | | BOTTOM OF REBOILER | DWG00012 | HL | |
| | PDT00030 | N-AREA RESIDUE | 2" | PLUG VALVE | | BOTTOM OF REBOILER | DWG00012 | HL | |
| | PDT00035 | N-AREA RESIDUE | 1" | PLUG VALVE | | MCT REBOILER TRANS F | DWG00012 | HL | |
| | PDT00040 | N-AREA RESIDUE | | PUMP | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00045 | N-AREA RESIDUE | | SAMPLE VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00050 | N-AREA RESIDUE | 1" | PLUG VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00055 | N-AREA RESIDUE | 3/4" | PLUG VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00056 | N-AREA RESIDUE | 3/4" | PLUG VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00058 | N-AREA RESIDUE | 3/4" | BALL VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| | PDT00060 | N-AREA RESIDUE | 2" | PLUG VALVE | | MCT REBOILER TRANS P | DWG00012 | HL | |
| * | PDT00065 | N-AREA RESIDUE | 2" | PLUG VALVE | | ABOVE REBOILER | DWG00012 | HL | |
| | PDT00070 | N-AREA RESIDUE | 2" | CONTROL VALVE | | ABOVE REBOILER | DWG00012 | HL | |
| | PDT00075 | N-AREA RESIDUE | 1" | PLUG VALVE | | NORTH SIDE REBOILER | DWG00012 | HL | |
| | PDT00080 | N-AREA RESIDUE | 2" | PLUG VALVE | | NORTH SIDE REBOILER | DWG00012 | HL | |
| | PDT00085 | N-AREA RESIDUE | 1-1/2" | PLUG VALVE | | EAST OF RES TANK | DWG00011 | HL | |
| | PDT00090 | N-AREA RESIDUE | 1-1/2" | BALL VALVE | | TOP MCT RESIDUE TANK | DWG00011 | HL | |
| | PDT00095 | N-AREA RESIDUE | 1-1/2" | BALL VALVE | | TOP MCT RESIDUE TANK | DWG00011 | HL | |
| | PDT00100 | N-AREA RESIDUE | 1/2" | PLUG VALVE | | TOP MCT RESIDUE TANK | DWG00011 | HL | |
| | PDT00110 | N-AREA RESIDUE | 2" | PLUG VALVE | | TOP MCT RESIDUE TANK | DWG00011 | HL | |
| | PDT00115 | N-AREA RESIDUE | 2" | PLUG VALVE | | STOR TK RECIRC LINE | DWG00011 | HL | |
| | PDT00120 | N-AREA RESIDUE | 2" | PLUG VALVE | | ABOVE MCT RES PUMP | DWG00011 | HL | |
| | PDT00125 | N-AREA RESIDUE | 2" | PLUG VALVE | | RECIRC LINE | DWG00011 | HL | |
| | PDT00130 | N-AREA RESIDUE | 2" | PLUG VALVE | | ABOVE RES TRANS PUMP | DWG00011 | HL | |
| | PDT00135 | N-AREA RESIDUE | 3/4" | PLUG VALVE | | ABOVE RES TRANS PUMP | | HL | |
| | PDT00140 | N-AREA RESIDUE | 1" | PLUG VALVE | | EAST OF RES TANK | DWG00011 | HL | |
| | PDT00145 | N-AREA RESIDUE | 1 1/2" | PLUG VALVE | | EAST OF RES TANK | | HL | |
| | PDT00150 | N-AREA RESIDUE | 2" | PLUG VALVE | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 1 1/2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | PLUG VALVE | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | PLUG VALVE | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | BALL VALVE | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | N-AREA RESIDUE | 2" | PLUG VALVE | | BOT MCT RESIDUE TK | DWG00011 | | |
| | | N-AREA RESIDUE | 2" | | | | | | |
| | | N-AREA RESIDUE | 2" | FLANGED FITTINGS | | TRAILER LOADING | DWG00013 | | |
| | | | | PLUG VALVE | | MCT RESIDUE TRANS PU | | | |
| | | N-AREA RESIDUE | 1" | PLUG VALVE | | MCT RESIDUE TRANS PU | | | |
| | PDT00185 | N-AREA RESIDUE | 1 1/2" X 3" | PUMP | | MCT RESIDUE TRANS PU | DWG00011 | H_ | |

| • | | _===== | Fa | Component | LOCATION | Iso | Clas |
|------|------------|--------|------------|------------------|----------------------|----------|------|
| | Unit | | Eq Size | Component | 200.1.20.7 | 130 | |
| | | | | | | | |
| | N-AREA RES | IDUE | 3/4" | PLUG VALVE | ABOVE RES TRANS PUMP | DWG00011 | HL |
| 2000 | N-AREA RES | IDUE | 3" | PLUG VALVE | SOUTH SIDE RES TANK | DWG00011 | HL |
| | N-AREA RES | IDUE | 2" | FLANGED FITTINGS | STOR TK RECIRC LINE | DWG30011 | HL |
| | N-AREA RES | IDUE | 2" | FLANGED FITTINGS | STOR TK RECIRC LINE | DWG00011 | HL |
| | N-AREA RES | IDUE | 1/2" | BALL VALVE | PUMP DISCHARGE | DWG00011 | HL |
| | N-AREA RES | IDUE | 1/2" | BALL VALVE | PUMP DISCHARGE . | DWG00011 | HL |
| | N-AREA RES | IDUE | 1/2" | BALL VALVE | PUMP DISCHARGE | DWG00011 | HL |
| | N-AREA RES | IDUE | 1/2" | BALL VALVE | PUMP DISCHARGE | DWG00011 | HL |
| | N-AREA RES | IDUE | 2" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | HL |
| | N-AREA RES | IDUE | 1 1/2" | FLANGED FITTINGS | MCT RESIDUE TRANS PU | DWG00011 | HL |
| | N-AREA RES | IDUE | 2" | PLUG VALVE | MCT RESIDUE DECANT T | DWG00011 | HL |
| | N-AREA RES | IDUE | 2" | FLANGED FITTINGS | MCT RESIDUE DECANT T | DWG00011 | HL |
| | N-AREA RES | | 1" | BALL VALVE | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 1/2" | BALL VALVE | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | PLUG VALVE | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | HL |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | RUPTURE DISC | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | TOP MCT RESIDUE TANK | DWG00011 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | N-AREA RES | | | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | G/V |
| | N-AREA RES | | 4" | | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| * | N-AREA RES | | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | | 4" | FLANGED FITTINGS | | DWG00014 | |
| | N-AREA RES | SIDUE | 4" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RES | SIDUE | 3 " | FLANGED FITTINGS | VENT LINE TO N-20 | | |
| | N-AREA RES | SIDUE | 2 " | FLANGED FITTINGS | ABOVE MCT RES PUMP | DWG00011 | |
| | N-AREA RES | SIDUE | 2" | FLANGED FITTINGS | ABOVE MCT RES PUMP | DWG00011 | |
| | N-AREA RE | SIDUE | 2" | FLANGED FITTINGS | ABOVE MCT RES PUMP | DWG00011 | |
| | N-AREA RE | SIDUE | 1" | FLANGED FITTINGS | VENT LINE TO N-20 | EWG00014 | |
| | N-AREA RE | SIDUE | 1" | PLUG VALVE | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RE | SIDUE | 1" | FLANGED FITTINGS | VENT LINE TO N-20 | DWG00014 | |
| | N-AREA RE | SIDUE | 1" | BALL VALVE | VENT LINE TO N-20 | EWG00014 | |
| | N-AREA RE | SIDUE | 3" | PLUG VALVE | VENT LINE TO N-20 | EWG30014 | |
| | N-AREA RE | SIDUE | 3 " | PLUG VALVE . | VENT LINE TO N-20 | DWG00014 | G/V |

RCRA SUBPART BB EQUIPMENT LIST

| | | | | *********** | | | | | | |
|----|----------|----------|--------|-------------|-----------|----------|--------------|----------|----------|---------------|
| | Tag | Unit | | Eq Size | Compone | nt | LOCATION | | Iso | Class |
| | | | | | | | | | | |
| | PDT00475 | N-AREA R | ESIDUE | 1/2" | BALL VAL | VE | NORTH SIDE R | EBOILER | DWG00012 | HL |
| | PDT00480 | N-AREA R | ESIDUE | 1/2" | BALL VAL | VE | NORTH SIDE R | EBOILER | DWG00012 | HL |
| | PDT00485 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | EAST OF MCT | STOR TK | DWG00011 | G/V |
| | PDT00490 | N-AREA R | ESIDUE | 3 " | FLANGED | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00495 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00500 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00505 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | |
| | PDT00510 | N-AREA R | ESIDUE | 3 " | FLANGED | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00515 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | |
| | PDT00520 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | |
| | PDT00525 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | 1000 |
| | PDT00530 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | SOUTH SIDE R | | | HL |
| | PDT00535 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | SOUTH SIDE R | | DWG00011 | HL |
| | PDT00540 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | TOP MCT RESI | | DWG00011 | |
| | PDT00545 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | TOP MCT RESI | | DWG00011 | |
| | PDT00550 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | TOP MCT RESI | | DWG00011 | |
| 95 | PDT00555 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | TOP MCT RESI | DUE TANK | DWG00011 | |
| | PDT00560 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | TOP MCT RESI | DUE TANK | DWG00011 | |
| | PDT00565 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00570 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | Area Art hard |
| | PDT00575 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | VENT LINE TO | N-20 | DWG00014 | |
| | PDT00580 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00585 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00590 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | VENT LINE TO | N-20 | DWG00014 | 200 |
| | PDT00595 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | VENT LINE TO | N-20 | | G/V |
| | PDT00600 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | VENT LINE TO | N-20 | DWG00014 | G/V |
| | PDT00610 | N-AREA R | ESIDUE | 2" | FLANGED : | FITTINGS | TOP OF MCT R | ESIDUE T | DWG00011 | |
| | PDT00612 | N-AREA R | ESIDUE | 3" | FLANGED : | FITTINGS | MCT RESIDUE | DECANT T | DWG00011 | |
| | PDT00614 | N-AREA R | ESIDUE | 10" | FLANGED : | FITTINGS | MCT RESIDUE | DECANT T | DWG00011 | HL |
| | PDT00615 | N-AREA R | ESIDUE | 1" | FLANGED : | FITTINGS | TOP OF MCT R | ESIDUE T | DWG00011 | G/V |
| | PDT00620 | N-AREA R | ESIDUE | 1" | FLANGED : | FITTINGS | TOP OF MCT R | ESIDUE T | DWG00011 | G/V |
| | PDT00625 | N-AREA R | ESIDUE | 2" | PLUG VAL | VE | MCT RESIDUE | DECANT T | DWG00011 | HL |
| | PDT00630 | N-AREA R | ESIDUE | 2" | PLUG VAL | VE | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00632 | N-AREA R | ESIDUE | 2" | FLANGED | FITTINGS | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00634 | N-AREA R | ESIDUE | 2" | FLANGED | FITTINGS | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00635 | N-AREA R | ESIDUE | 3/4" | PLUG VAL | VE | ABOVE RES TR | ANS PUMP | DWG00011 | HL |
| | PDT00640 | N-AREA R | ESIDUE | 3/4" | PLUG VAL | VE | ABOVE RES TR | ANS PUMP | DWG00011 | HL |
| | PDT00642 | N-AREA R | ESIDUE | 3" | FLANGED | FITTINGS | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00644 | N-AREA R | ESIDUE | 2" | FLANGED | FITTINGS | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00645 | N-AREA R | ESIDUE | 2" | PLUG VAL | VE | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00650 | N-AREA R | ESIDUE | 3" | PLUG VAL | VE | MCT RESIDUE | DECANT T | DWG00011 | HL |
| | PDT00652 | N-AREA R | ESIDUE | 2" | FLANGED | FITTINGS | MCT RESIDUE | TRANS PU | DWG00011 | HL |
| | PDT00655 | N-AREA R | ESIDUE | 2" | PLUG VAL | VE | MCT RESIDUE | DECANT T | DWG00011 | HL |
| | | RESIDUE | BURNER | 2" | BALL VAL | VE | T-20 NAPL S | TORAGE | DWG00015 | :: |
| | | RESIDUE | | 1" | FLANGED | FITTINGS | T-20 NAPL S | TORAGE | DWG00015 | LL |
| | PCH00009 | RESIDUE | BURNER | 1" | FLANGED | FITTINGS | T-20 NAPL S | TORAGE | DWG00015 | LL |
| | | RESIDUE | | 1" | PLUG VAL | VE VE | T-20 NAPL S | TORAGE | DWG00015 | LL |
| / | | RESIDUE | | 1" | FLANGED | FITTINGS | T-20 NAPL S | TORAGE | DWG00015 | LL |
| | | RESIDUE | | 1" | PLUG VAL | VE | T-20 NAPL S | TORAGE | DWG00015 | LL |
| | | | | | | | | | | |

| | ********* | ****** | | ************ | | | | | | |
|---|-----------|---------|--------|----------------|-----------------|------|-------------|---------|----------|-------|
| | Tag | Unit | | Eq | Component | | LOCATION | | Iso | Class |
| | | | | Size | | | | | | |
| | | | | | | | | | | |
| | POH00020 | RESIDUE | BURNER | ,1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00025 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00030 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00032 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00035 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00040 | RESIDUE | BURNER | 3 " | CONTROL VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | PCH00045 | RESIDUE | BURNER | 1" | VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00050 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00055 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00060 | RESIDUE | BURNER | 3" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00065 | RESIDUE | BURNER | 3" | CHECK VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00070 | RESIDUE | BURNER | 1/2" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00075 | RESIDUE | BURNER | 3" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | PCH00080 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00085 | RESIDUE | BURNER | 1 1/2 X 3 X 10 | PUMP | | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00090 | RESIDUE | BURNER | 1" | FLANGED FITTING | GS | T-20 NAPL | STORAGE | DWG00015 | LL |
| | POH00094 | RESIDUE | BURNER | 1" | FLANGED FITTING | GS * | T-20 NAPL | STORAGE | DWG00015 | LL |
| | PCH00095 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL | | DWG00015 | LL |
| | POH00096 | RESIDUE | BURNER | 1" | FLANGED FITTING | GS | T-20 NAPL S | STORAGE | DWG00015 | LL |
| | РОН00098 | RESIDUE | BURNER | 1" | FLANGED FITTING | | T-20 NAPL S | | DWG00015 | LL |
| | POH00100 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00105 | RESIDUE | BURNER | 2" | VALVE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00110 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00112 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00115 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00120 | RESIDUE | BURNER | 1" | PRESSURE RELIE | | T-20 NAPL S | | DWG00015 | LL |
| | POH00125 | RESIDUE | BURNER | 1" | BLOCK&BLEED VAL | LVE | T-20 NAPL S | STORAGE | DWG00015 | LL |
| | PCH00130 | RESIDUE | BURNER | 1" | BLOCK&BLEED VAI | LVE | T-20 NAPL S | STORAGE | DWG00015 | LL |
| | PCH00135 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | STORAGE | DWG00015 | LL |
| | POH00140 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | STORAGE | DWG00017 | LL |
| | POH00142 | RESIDUE | BURNER | 6" | FLANGED FITTING | 3S | TOP OF T-20 |) | DWG00017 | LL |
| | POH00144 | RESIDUE | | 2" | FLANGED FITTING | | TOP OF T-20 | | DWG00017 | LL |
| | POH00145 | RESIDUE | BURNER | 2" | CONTROL VALVE | | T-20 NAPL S | | | LL |
| | POH00150 | RESIDUE | BURNER | 3" | CONTROL VALVE | | T-20 NAPL S | STORAGE | DWG00016 | LL |
| | POH00155 | RESIDUE | BURNER | 3/4" | SAMPLE VALVE | | T-20 NAPL S | STORAGE | DWG00016 | LL |
| | POH00160 | RESIDUE | BURNER | 3" | VALVE | | T-20 NAPL S | STORAGE | DWG00015 | LL |
| | POH00165 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-20 NAPL S | STORAGE | DWG00017 | LL |
| | POH00157 | RESIDUE | BURNER | 6" | FLANGED FITTING | | TOP OF T-20 | | DWG00017 | LL |
| | PCH00169 | RESIDUE | BURNER | 2" | FLANGED FITTING | | TOP OF T-20 | | DWG00017 | |
| | PCH00170 | RESIDUE | | 2" | PLUG VALVE | | T-20 NAPL S | | | LL |
| | PCH00172 | RESIDUE | | 3" | FLANGED FITTING | | TOP OF T-20 | | DWG00017 | G/V |
| | PCH00175 | RESIDUE | | 1/2" | PLUG VALVE | | T-20 NAPL S | | | LL |
| | POH00180 | RESIDUE | | 2" | PLUG VALVE | | T-20 NAPL S | | DWG00019 | |
| | POH00131 | RESIDUE | | 2" | FLANGED FITTING | | T-20 NAPL S | | DWG00019 | |
| | POH00135 | RESIDUE | | 2" | PLUG VALVE | | T-20 NAPL S | | DWG00019 | |
| | POH00190 | RESIDUE | | 1/2" | PLUG VALVE | | T-20 NAPL S | | DWG00019 | |
| | POH00196 | RESIDUE | | 2" | FLANGED FITTING | | T-20 NAPL S | | DWG00019 | |
| / | PCHC0198 | RESIDUE | | 2" | FLANGED FITTING | | T-20 NAPL 6 | | DWG00019 | |
| | PCH30200 | RESIDUE | | 1" | BALL VALVE | | T-20 NAPL S | | DWG00019 | |
| | | | | 77. | | | | | | |

| Tag | Unit | Eq | Component | LOCATION | Iso | Class |
|----------------------|---------------|---------|-----------------------|----------------------|----------|-------|
| | | Size | | | 130 | C1033 |
| | | | | | | |
| PCH00202 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00204 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00205 | RESIDUE BURNE | ER 3/4" | SAMPLE VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00206 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00208 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00210 | RESIDUE BURNE | ER 2" | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00212 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00214 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00215 | RESIDUE BURNE | ER 2" | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00216 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00217 | RESIDUE BURNE | ER 2" | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00218 | RESIDUE BURNE | | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00220 | RESIDUE BURNE | ER 2" | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00225 | RESIDUE BURNE | ER 1" | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00230 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00235 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00237 | RESIDUE BURNE | | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00239 | RESIDUE BURNE | | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00240 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00242 | RESIDUE BURNE | | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00244 | RESIDUE BURNE | | FLANGED FITTINGS | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00245 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00019 | LL |
| POH00250 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00015 | LL |
| POH00255 | RESIDUE BURNE | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | LL |
| POH00260 | RESIDUE BURNE | | NAPL PUMP | T-20 NAPL STORAGE | DWG00016 | LL |
| POH00265 | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | DWG00016 | LL |
| | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | DWG00016 | LL |
| POH00270 | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | DWG00016 | LL |
| POH00275 POH00280 | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | DWG00016 | LL |
| | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | DWG00016 | LL |
| POH00285 | RESIDUE BURNE | | PLUG VALVE | T-20 BURNER FEED | | LL |
| POH00295 | | | PRESSURE RELIEF VALVE | T-20 BURNER FEED | DWG00016 | LL |
| POH00300 | RESIDUE BURNE | | PLUG VALVE | T-4,T-6 & T-20 BURN | | LL |
| POH00305 | RESIDUE BURNE | | BALL VALVE | T-4, T-6 & T-20 BURN | DWG00028 | |
| POH00310 | RESIDUE BURNI | | GATE VALVE | T-4,T-6 & T-20 BURN | DWG00028 | |
| | RESIDUE BURNE | | | T-4, T-6 & T-20 BURN | DWG00028 | |
| | RESIDUE BURNE | | BALL VALVE | T-4,T-6 & T-20 BURN | DWG00028 | |
| | RESIDUE BURNI | | | T-4,T-6 & T-20 BURN | DWG00028 | |
| | RESIDUE BURNI | | BALL VALVE | T-4,T-6 & T-20 BURN | DWG00028 | |
| | RESIDUE BURN | | BALL VALVE | T-4,T-6 & T-20 BURN | DWG00029 | |
| | RESIDUE BURNI | | BALL VALVE | | DWG00025 | |
| PCH00400 | RESIDUE BURNI | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | |
| POH00405 | RESIDUE BURN | | BALL VALVE | T-20 NAPL STORAGE | | |
| POH00409 | RESIDUE BURNI | | BALL VALVE | T-4,T-6 & T-20 BURN | DWG00028 | |
| POH00409 | RESIDUE BURN | | BALL VALVE | T-4,T-6 & T-20 BURN | | |
| POH00413 | RESIDUE BURNI | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | |
| | RESIDUE BURN | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | |
| | RESIDUE BURN | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | |
| | RESIDUE BURNI | | PLUG VALVE | T-20 NAPL STORAGE | DWG00016 | |
| PCH00423 | RESIDUE BURN | ER 2" | PLUG VALVE | T-6 STORAGE | DWG00030 | 22 |
| | | | | | | |

| | | | Fa | | TOCOMTON | | |
|---|----------|----------------|-------------|-----------------|---------------------|----------|-------|
| | Tag | Unit | Eq Size | Component | LOCATION | Iso | Class |
| _ | | | | | | | |
| | POH00425 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 STORAGE | DWG00030 | LL |
| | POH00430 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00432 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00435 | RESIDUE BURNER | 2" | CHECK VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00440 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00445 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00450 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00455 | RESIDUE BURNER | 1"X1-1/2"x8 | PUMP #6PCBTF | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00460 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00465 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00470 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00023 | LL |
| | POH00475 | RESIDUE BURNER | 3/4" | BALL VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00480 | RESIDUE BURNER | 3/4" | BALL VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00485 | RESIDUE BURNER | 1/2" | BALL VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00490 | RESIDUE BURNER | 1/2" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00495 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00500 | RESIDUE BURNER | 2" | BALL VALVE | T-6 TRAILER UNLOADI | DWG00029 | LL |
| | POH00505 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00510 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00515 | RESIDUE BURNER | 3" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00520 | RESIDUE BURNER | 2" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00525 | RESIDUE BURNER | 2" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00530 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00535 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00540 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00545 | RESIDUE BURNER | | PCBTF FEED PUMP | T-6 BURNER FEED | DWG00031 | LL |
| | POH00550 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00555 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00560 | RESIDUE BURNER | 1/2" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00565 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00570 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00575 | RESIDUE BURNER | 1" | BALL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00577 | RESIDUE BURNER | 1" | CONTROL VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00590 | RESIDUE BURNER | 3" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00595 | RESIDUE BURNER | 1" | PLUG VALVE | T-6 BURNER FEED | DWG00031 | LL |
| | POH00600 | RESIDUE BURNER | 3 " | PLUG VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00605 | RESIDUE BURNER | 2" | PLUG VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00610 | RESIDUE BURNER | 2" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00615 | RESIDUE BURNER | 1" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00620 | RESIDUE BURNER | 2" | PLUG VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00625 | RESIDUE BURNER | 2" | PLUG VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00635 | RESIDUE BURNER | 2" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | PCH00640 | RESIDUE BURNER | 1" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | PCH00645 | RESIDUE BURNER | | PUMP | T-1 BURNER FEED | DWG00022 | LL |
| | POH00650 | RESIDUE BURNER | 2" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00655 | RESIDUE BURNER | 1" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00660 | RESIDUE BURNER | 1" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| 1 | POH00665 | RESIDUE BURNER | 1" | BALL VALVE | T-1 BURNER FEED | DWG00022 | LL |
| | POH00670 | RESIDUE BURNER | 1" | CONTROL VALVE | T-1 BUPNER FEED | DWG00022 | LL |
| | | | | | | | |

RCRA SUBPART BB EQUIPMENT LIST

| 4==== | | | | *********** | | ******** | | ******* | | |
|-------|----------|---------|--------|-------------|-----------------|-----------|---------------|---------|----------|-------|
| | Tag | Unit | | Eq | Component | | LCCATION | | Iso | Class |
| | | | | Size | | | | | | |
| | | | | | | | | | | |
| | POH00672 | RESIDUE | BURNER | 1" | BALL VALVE | | T-1 BURNER F | EED | DWG00022 | LL |
| | POH00674 | RESIDUE | BURNER | 1" | BALL VALVE | | T-1 BURNER F | EED | DWG00022 | LL |
| | POH00676 | RESIDUE | BURNER | 1" | BALL VALVE | | T-1 BURNER FI | EED | DWG00022 | LL |
| | POH00678 | RESIDUE | BURNER | 1" | FLANGED FITTING | S | T-1 FEED TO | BURNER | DWG00022 | LL |
| | POH00680 | RESIDUE | BURNER | 1" | PRESSURE RELIEF | VALVE | T-1 BURNER F | EED | DWG00022 | LL |
| | POH00682 | RESIDUE | BURNER | 1" | FLANGED FITTING | S | T-1 FEED TO E | BURNER | DWG00022 | LL |
| | POH00690 | RESIDUE | BURNER | 1/2" | BALL VALVE | | T-1 BURNER F | EED | DWG00022 | LL |
| | POH00695 | RESIDUE | BURNER | 2" | BALL VALVE | | T-1 BURNER F | EED | DWG00022 | LL |
| | POH00700 | RESIDUE | BURNER | 2" | BALL VALVE | | DIRECT FEED | FROM T/ | DWG00023 | LL |
| | POH00705 | RESIDUE | BURNER | 1/2" | BALL VALVE | | DIRECT FEED 1 | FROM T/ | DWG00023 | LL |
| | POH00710 | RESIDUE | BURNER | 1" | BALL VALVE | | DIRECT FEED I | FROM T/ | DWG00023 | LL |
| | POH00715 | RESIDUE | BURNER | 1/2" | BALL VALVE | | DIRECT FEED I | FROM T/ | DWG00023 | ĽĻ |
| | POH00720 | RESIDUE | BURNER | 1/2" | BALL VALVE | | DIRECT FEED I | FROM T/ | DWG00023 | LL |
| | POH00725 | RESIDUE | BURNER | 2" | BALL VALVE | | DIRECT FEED ! | FROM T/ | DWG00023 | LL |
| | POH00730 | RESIDUE | BURNER | 1" | BALL VALVE | | DIRECT FEED | FROM T/ | DWG00023 | LL |
| | POH00735 | RESIDUE | BURNER | 3" | PLUG VALVE | | T-1 STORAGE | | DWG00022 | LL |
| | POH00740 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-1 STORAGE | | DWG00022 | LL |
| | POH00745 | RESIDUE | BURNER | 1/2" | PLUG VALVE | | T-1 STORAGE | | DWG00022 | LL |
| | POH00746 | RESIDUE | BURNER | 1/2" | FLANGED FITTING | S | T-1 STORAGE | | DWG00022 | LL |
| | POH00748 | RESIDUE | BURNER | 1/2" | FLANGED FITTING | SS | T-1 STORAGE | | DWG00022 | LL |
| | POH00750 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-1 TRAILER U | UNLOADI | DWG00020 | LL |
| | POH00755 | RESIDUE | BURNER | | BOC PUMP | | T-1 TRAILER T | UNLOADI | DWG00020 | LL |
| | POH00760 | RESIDUE | BURNER | 1/2" | BALL VALVE | | T-1 TRAILER | JNLOADI | DWG00020 | LL |
| | POH00765 | RESIDUE | BURNER | 1/2" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00770 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-1 TRAILER U | JNLOADI | DWG00020 | LL |
| | POHC0775 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00780 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-1 TRAILER | JNLOADI | DWG00020 | LL |
| | PCH00782 | RESIDUE | BURNER | 2" | CHECK VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00785 | RESIDUE | BURNER | 1" | PLUG VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00790 | RESIDUE | BURNER | 1 1/2" | PLUG VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH20795 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00800 | RESIDUE | BURNER | 3/4" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00805 | RESIDUE | BURNER | 2" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00808 | RESIDUE | BURNER | 2" | PLUG VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00810 | RESIDUE | | 3/4" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00815 | RESIDUE | BURNER | 2" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00820 | RESIDUE | BURNER | 1/2" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | PCH00825 | RESIDUE | BURNER | 1/2" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00830 | RESIDUE | | 1" | BALL VALVE | | T-1 TRAILER | UNLOADI | DWG00020 | LL |
| | POH00835 | RESIDUE | | 3" | PLUG VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | POH00840 | RESIDUE | | 1" | PLUG VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | POH00845 | RESIDUE | | 1/2" | PLUG VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | POH00850 | RESIDUE | | 3" | PLUG VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | POH00855 | RESIDUE | | 2" | PLUG VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | PCH00860 | RESIDUE | | 2" | BALL VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | POH30373 | RESIDUE | | 1" | BALL VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | PCH30875 | RESIDUE | | 1" | BALL VALVE | | T-4 BURNER F | EED | DWG00027 | LL |
| | PCHOOSEO | RESIDUE | | | HEATED STORAGE | FEED PUMP | T-4 BURNER F | EED | DWG00027 | LL |
| | PCH00885 | RESIDUE | | 1/2" | BALL VALVE | | T-4 BURNER F | | DWG00027 | LL |
| | . 5 | | | (c) = | 77.00 | | | | | |